



Eyal MAG Ltd.

Phone: 972-9-7499100 Fax: 972-9-7493669

Kibbutz Eyal D.N. Hasharon Hatichon 45840 Israel

Web: www.eyal-mag.com Email: emi@eyal-emi.com




## **14 Watt LINEAR POWER AMPLIFIER WCDMA 2130 to 2170 MHz MODEL: LPA-4067-14**

### **General Description of the Power Amplifier**

This document specifies a 14 Watt WCDMA multicarrier Power Amplifier, Manufactured by EYAL MAG LTD,

### **Features:**



- **2130 to 2170 MHZFREQUENCY RANGE**
- **50 dB Gain**
- **14 W Output Power**
- **27 V DC Voltage Range**
- **- 20°C to +80°C Operating Temperature Range**
- **Alarms and interface per custom request**

### **INTRODUCTION**

This catalog

- Summarizes guaranteed amplifier performance specifications.
- Provides typical performance data on some of our more popular models.
- Categorizes options to our standard catalog designs.
- Provides detailed outline drawings on all catalog models.



Eyal MAG Ltd.

Phone: 972-9-7499100 Fax: 972-9-7493669

Kibbutz Eyal D.N. Hasharon Hatichon 45840 Israel

Web: www.eyal-mag.com Email: emi@eyal-emi.com



## **SPECIFICATION SUMMARY** **FOR PCS POWER AMPLIFIER 4067-14**

	Specification	Note
FREQUENCY RANGE	2130÷2170 MHz	
COMPOSITE AVERAGE OUTPUT POWER	41.5dBm	(14.0W)
GAIN	50 dB	± 1 dB
GAIN FLATNESS OVER FREQUENCY	± 0.75 dB	Max.
INPUT / OUTPUT VSWR	1.5:1	Max.
DC INPUT VOLTAGE	27V dc	
DC INPUT CURRENT	6A Max.	@ Pout = 14W
ABS Power at ± 2.25MHz, 14W 3 Carriers CDMA IS-95C	-13dBm / 1MHz	+ 25°C
IMD at +/- 750 kHz offset 14W, 3 carriers CDMA IS – 95C	-45dBc / 30kHz	+ 25°C
IMD at +/- 1.98 MHz offset 14W 3 carriers CDMA IS – 95C	-60dBc / 30kHz	+ 25°C

### **ALARMS AND SIGNAL**

ALARMS, FUNCTIONS	AUTO RECOVERY	Note
Overpower alarm at 46 dBm, 3 CDMA Carriers	Yes	
Reflected power alarm at 36-37 dBm, 3 CDMA Carriers	Yes	
Temperature Monitor, 500 mV+10mV / °C	Yes	
Over temperature alarm, 86°C	Yes	±2°C
Enable, active LOW	Yes	
Forward Power Monitor	2.4 ± 0.05V at 33dBm 4.8 ± 0.05V at 45 dBm	
Overpower shutdown	46 – 47 dBm	

### **PROTECTION SHUTDOWN**

Internal Temperature > 85°C, auto restart at 75°C	Yes	±2°C
Overpower at 47-48 dBm enable to restart	Yes	
Over voltage 28.5V	Yes	